




Product # 1169-1101



**COLLECTION | CHEVRON**  
**COLOR | NATURAL**

Wood species | Oak  
Grade | Select & Better  
Constructions | 3-layer T&G Engineered Flooring  
Size | 15 x 107,95 x 530 mm (5/8" x 4 1/4" x 20 7/8")  
Finish | Lacquer CosNanoTech+

## CONSTRUCTION : 3-LAYER T&G ENGINEERED FLOORING

DIMENSIONS :			PACKAGING :		
			BOX	PALLET	
Thickness	15 mm (5/8")		Content:	1,72 m <sup>2</sup>	42 (72,24 m <sup>2</sup> )
Width	107,95 mm (4 1/4")		Weight	18 kg	764 kg
Length	530 mm (20 7/8")		H x W x L	151 x 338 x 675 mm	1061 x 680 x 2020 mm
Cut angle	45°		Content:	18,51 sq.ft.	777,30 sq.ft.
Microbevel	0,5 mm		Weight	40 lb	1691 lb
Joint type	tongue and groove (T&G)	H x W x L	6" x 14" x 27"	42" x 27" x 80"	

## DEVIATIONS :

Deviation on Thickness	± 0,2 mm	EN 13489
Deviation on Width	± 0,2 mm	
Height Difference	≤ 0,2 % of width	ГОСТ 862.3
Cup	≤ 0,2 % of plank width	СТБ 2121
Bow	≤ 0,1 % of length	EN 13489
Spring	≤ 0,5 % of length	

## CHARACTERISTICS :

Fire resistance	Dfl-s1	EN 14342
Formaldehyde emission class	E1	
Pentachlorophenol content	None	
Thermal resistance	0,095 m <sup>2</sup> ·K/W	
Thermal conductivity	0,158 W/(m·K)	
Structural warranty	Lifetime	

## INSTALLATION :



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.  
Applicable above, on and below ground level.

## STORAGE AND USAGE :



— Air humidity 40% – 65%  
— Temperature +18 °C – +22 °C

## FINISH : LACQUER CosNanoTech+

DESCRIPTION :	
Type of coating	UV-curable polyurethane-acrylate with micro-corundum
Surface (finish) type	Closed pores
Sheen	Semigloss 30-40 GU/60°
Finish warranty	25 years

## CLASSIFICATION SURFACE CHARACTERISTICS :

Wear resistance	Taber Test - 500 turns (S 42; 1000 gr)	EN 438-2
Scratch resistance	Rating 3	EN 438
Slip resistance	46 (SRV dry)	EN 15676
Resistance to chemical agents	Class 5 (Except blue ink)	EN 13442
Repairability	Low	

## MAINTENANCE AND CARE CONDITIONS :

Maintenance of hardwood floors with lacquer CosNanoTech+ finish assumes regular (daily if necessary) cleaning from dust and dirt using a vacuum, followed by a thorough cleaning using Coswick hardwood floor cleaner or other similar product. Due to high wear resistance properties, CosNanoTech+ lacquer finish does not require any additional care or finish renewal throughout the entire life of the floor.

## GRADE : SELECT & BETTER

DESCRIPTION :		DESCRIPTION :	
Sound sapwood	Permitted to 25% of the plank area	Bark pocket	Permitted up to 10 mm in length, up to 3 mm in width, filled
Colour variation	Permitted slight colour variation	Pith	Permitted healthy heart
Knot	Permitted up to 10 mm, filled	Slope of grain	Permitted
Checks	Not permitted	Medullary ray	Permitted