



COLLECTION | MOSAIC FLOORS
COLOR | NATURAL
 Wood species | Ash
 Grade | Select & Better
 Pattern | Provence
 Constructions | 2-layer T&G
 Size | 16,0 x 431 x 431 mm (5/8" x 17" x 17")
 Finish | Resilient Lacquer

CONSTRUCTION : 2-LAYER T&G

DIMENSIONS :			PACKAGING :	
			BOX	PALLET
Thickness	16,0 mm (5/8")		Content: 1,488 m ²	40 (59,52m ²)
Width	431 mm (17")		Weight 17 kg	702 kg
Length	431 mm (17")		H x W x L 131 x 448 x 460 mm	780 x 930 x 1800 mm
Average length	-		Content: 16,0 sq.ft.	640 sq.ft.
Microbevel	-		Weight 38 lb	1552 lb
Joint type	tongue and groove (T&G)	H x W x L 5" x 18" x 19"	31" x 37" x 71"	

DEVIATIONS :

Deviation on Thickness	± 0,2 mm	
Deviation on Width	± 0,3 mm	EN 13489
Height Difference	≤ 0,04 % of width	ГОСТ 862.3
Cup	≤ 0,2 % of plank width	СТБ 2121
Bow	-	
Spring	≤ 0,5 % of length	EN 13489

CHARACTERISTICS :

Fire resistance	Dfl-s1	
Formaldehyde emission class	E1	
Pentachlorophenol content	None	EN 14342
Thermal resistance	0,104 m ² ·K/W	
Thermal conductivity	0,154 W/(m·K)	
Structural warranty	Lifetime	

INSTALLATION :



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.
Applicable above, on and below ground level.

STORAGE AND USAGE :



— Air humidity 40% – 65%
— Temperature +18 °C – +22 °C

FINISH : RESILIENT LACQUER

DESCRIPTION :	
Type of coating	UV-cured modified polyurethane-acrylate
Surface (finish) type	Semi-closed pores
Sheen	Semigloss 15 - 22 GU/60°
Finish warranty	-

CLASSIFICATION SURFACE CHARACTERISTICS :

Wear resistance	Not rated	EN 438-2
Scratch resistance	Not rated	EN 438
Slip resistance	52 (SRV dry)	EN 15676
Resistance to chemical agents	Class 5 (Except blue ink)	EN 13442
Repairability	Medium	

MAINTENANCE AND CARE CONDITIONS :

Maintenance of hardwood floors with Resilient Lacquer finish assumes regular (daily if necessary) cleaning from dust and dirt using a vacuum, followed by a thorough cleaning using Coswick hardwood floor cleaner or other similar product.

GRADE : SELECT & BETTER

DESCRIPTION :		DESCRIPTION :	
Sound sapwood	Permitted to 25% of the plank area	Bark pocket	Permitted up to 10 mm in length, up to 3 mm in width, filled
Colour variation	Permitted slight colour variation	Pith	Permitted healthy heart
Knot	Permitted up to 10 mm, filled	Slope of grain	Permitted
Checks	Not permitted	Medullary ray	Permitted