



COLLECTION | MOSAIC FLOORS
COLOR | OLD VENICE
 Wood species | Oak
 Grade | Select & Better
 Pattern | Langeais
 Constructions | 2-layer T&G
 Size | 19,05 x 635 x 635 mm (¾" x 25" x 25")
 Finish | Hardwax Oil Combi

CONSTRUCTION : 2-LAYER T&G

| DIMENSIONS : | | | PACKAGING : | | |
|----------------|-------------------------|-----------|----------------|---------------------|----------------------------|
| | | | BOX | PALLET | |
| Thickness | 19,05 mm (¾") | | Content: | 1,61 m ² | 27 (43,47 m ²) |
| Width | 635 mm (25") | | Weight | 21 kg | 602 kg |
| Length | 635 mm (25") | | H x W x L | 85 x 648 x 660 mm | 900 x 680 x 1960 mm |
| Average length | - | | Content: | 17,32 sq.ft. | 467,64 sq.ft. |
| Microbevel | 1,0 mm | | Weight | 49 lb | 1332 lb |
| Joint type | tongue and groove (T&G) | H x W x L | 3" x 26" x 26" | 35" x 27" x 77" | |

DEVIATIONS :

| | | |
|------------------------|------------------------|------------|
| Deviation on Thickness | ± 0,2 mm | EN 13489 |
| Deviation on Width | ± 0,3 mm | |
| Height Difference | ≤ 0,04 % of width | ГОСТ 862.3 |
| Cup | ≤ 0,2 % of plank width | СТБ 2121 |
| Bow | - | EN 13489 |
| Spring | ≤ 0,5 % of length | |

CHARACTERISTICS :

| | | |
|-----------------------------|---------------------------|----------|
| Fire resistance | Dfl-s1 | EN 14342 |
| Formaldehyde emission class | E1 | |
| Pentachlorophenol content | None | |
| Thermal resistance | 0,128 m ² ·K/W | |
| Thermal conductivity | 0,148 W/(m·K) | |
| Structural warranty | Lifetime | |

INSTALLATION :



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.
Applicable above, on and below ground level.

STORAGE AND USAGE :



— Air humidity 40% – 65%
— Temperature +18 °C – +22 °C

FINISH : HARDWAX OIL COMBI

| DESCRIPTION : | |
|-----------------------|--|
| Type of coating | UV-cured modified polyurethane-acrylate, organic oils and waxes, oxidative |
| Surface (finish) type | Semi-closed pores, wire brushed |
| Sheen | Silk matte 6 - 12 GU/85° |
| Finish warranty | - |

CLASSIFICATION SURFACE CHARACTERISTICS :

| | | |
|-------------------------------|---------------------------|----------|
| Wear resistance | Not rated | EN 438-2 |
| Scratch resistance | Not rated | EN 438 |
| Slip resistance | 50 (SRV dry) | EN 15676 |
| Resistance to chemical agents | Class 5 (Except blue ink) | EN 13442 |
| Repairability | High | |

MAINTENANCE AND CARE CONDITIONS :

Maintenance of hardwood floors with Hardwax Oil Combi finish assumes regular (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with Coswick Hardwood Floor Cleaner or other similar product. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc., should be periodically renewed with special Coswick Restorative Oil. This product restores the protective surface film. Frequency of use depends on type of interior and intensity of foot traffic. For residential interiors, restorative cleaning should be done once in 3-5 years; for public and commercial interiors with intense foot traffic, it is recommended to use the product 2-4 times a year.

GRADE : SELECT & BETTER

| DESCRIPTION : | | DESCRIPTION : | |
|------------------|------------------------------------|----------------|--|
| Sound sapwood | Permitted to 25% of the plank area | Bark pocket | Permitted up to 10 mm in length, up to 3 mm in width, filled |
| Colour variation | Permitted slight colour variation | Pith | Permitted healthy heart |
| Knot | Permitted up to 10 mm, filled | Slope of grain | Permitted |
| Checks | Not permitted | Medullary ray | Permitted |