



**AMERICAN WALNUT COLLECTION  
DECOR | SUNSET**

**Wood species** American Walnut  
**Selection |** 1 Natur  
**Pattern |** Elsinore  
**Constructions** 3-layer flooring T&G  
**Size |** 19,05x185,28x530.72 mm (3/4"x7 5/16"x20 7/8")  
**Finish |** Silk mat finish

**CONSTRUCTION: 3-LAYER FLOORING T&G**

DIMENSIONS :			PACKAGING :	
			BOX	PALLET
Thickness	19,05 mm (3/4")	Content	1,38 m2	30 box (41,4 m2)
Width	185,28 mm (7 5/16")	Weigh	17 kg	540 kg
Length	530.72 (20 7/8")	H x W x L	x x mm	x x mm
Average length		Content	14,849 sq.ft.	445,464 sq.ft.
Microbevel	0,5 mm	Weigh	18 lb	564 lb
Joint type	T&G	H x W x L	x x mm	x x mm

**CHARACTERISTICS:**

Fire resistance	Dfl-s1	EN 14342
Formaldehyde emission class	E1	
Pentachlorophenol content	None	
Thermal resistance	0,118 m2-K/W	
Thermal conductivity	0,161 W/(m-K)	
Structural warranty	Lifetime	

**INSTALLATION :**



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor. Applicable above, on and below ground level.

**STORAGE AND USAGE :**



— Air humidity 40% – 65%  
 — Temperature +18 °C – +22 °C

**FINISH : SILK MAT FINISH**

DESCRIPTION	
Type of coating	UV-cured modified polyurethane-acrylate
Surface (finish) type	Semi-closed pores, wire brushed
Sheen	Matte, 2–5 GU/60°
Finish warranty	-

**CLASSIFICATION SURFACE CHARACTERISTICS:**

Wear resistance	Not rated	EN 438-2
Scratch resistance	Not rated	EN 438
Slip resistance	50 (SRV dry)	EN 15676
Resistance to chemical agents	Class 5 (Except blue ink)	EN 13442
Repairability	Medium	

**MAINTENANCE AND CARE CONDITIONS :**

Maintenance of hardwood floors with Silk finish assumes regular (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with Coswick Hardwood Floor Cleaner or other similar product. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc., should be periodically renewed with special Coswick Restorative Oil. This product restores the protective surface film. Frequency of use depends on type of interior and intensity of foot traffic. For residential interiors, restorative cleaning should be done once in 3-5 years; for public and commercial interiors with intense foot traffic, it is recommended to use the product 2-4 times a year.

**SELECTION 1 NATUR**

DESCRIPTION:		DESCRIPTION:	
Sound sapwood	No limit	Bark pocket	Permitted up to 50 mm in length, up to 5 mm in width, filled
Colour variation	No limit	Pith	Permitted
Knot	Permitted up to 60 mm, filled	Slope of grain	Permitted
Cracks	Permitted narrow, filled	Medullary ray	Permitted

COSWICK Ltd.

2B Kolasa Str., 223034 Zaslavl, Republic of Belarus

Tel.: +375-17-543-2012, Fax: +375-17-543-2020, E-mail: sales@coswick.com

www.coswick.com

