



COLLECTION | UNIBLOCK FLOORING
COLOR | ROSE

Wood species | Oak
Grade | Select & Better
Pattern | Squares 4 bars
Constructions | Solid Hardwood Flooring T&G
Size | 19,05 x 228,6 x 228,6 mm (¾" x 9" x 9")
Finish | Lacquer CosNanoTech+

CONSTRUCTION : SOLID HARDWOOD FLOORING T&G

DIMENSIONS :			PACKAGING :	
			BOX	PALLET
Thickness	19,05 mm (¾")	Content:	0,731 m ²	72 (52,632 m ²)
Width	57,15 mm (2 ¼")	Weight	10 kg	720 kg
Length	228,6 mm (9")	H x W x L	140 x 252 x 488 mm	964 x 760 x 1970 mm
Squares 4 bars	228,6 x 228,6 mm (9" x 9")	Content:	7,87 sq.ft.	566,64 sq.ft.
Microbevel	0,5 mm	Weight	22 lb	1594 lb
Joint type	tongue and groove (T&G)	H x W x L	6" x 10" x 19"	38" x 30" x 78"

DEVIATIONS :

Deviation on Thickness	± 0,2 mm	EN 13226 ГОСТ 862.1 СТБ 1454
Deviation on Width	± 0,2 mm	
Height Difference	≤ 0,2 % of width	
Cup	≤ 0,2 % of plank width	EN 13226
Bow	≤ 0,5 % of length	
Spring	≤ 0,5 ‰ of length	

CHARACTERISTICS :

Fire resistance	Dfl-s1	EN 14342
Formaldehyde emission class	E1	
Pentachlorophenol content	None	
Thermal resistance	0,112 m ² ·K/W	
Thermal conductivity	0,170 W/(m·K)	
Structural warranty	Lifetime	

INSTALLATION :



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.
Applicable above and on ground level.

STORAGE AND USAGE :



— Air humidity 45% – 55%
— Temperature +18 °C – +22 °C

FINISH : LACQUER CosNanoTech+

DESCRIPTION :	
Type of coating	UV-curable polyurethane-acrylate with micro-corundum
Surface (finish) type	Closed pores
Sheen	Semigloss 30-40 GU/60°
Finish warranty	25 years

CLASSIFICATION SURFACE CHARACTERISTICS :

Wear resistance	Taber Test - 500 turns (S 42; 1000 gr)	EN 438-2
Scratch resistance	Rating 3	EN 438
Slip resistance	46 (SRV dry)	EN 15676
Resistance to chemical agents	Class 5 (Except blue ink)	EN 13442
Repairability	Low	

MAINTENANCE AND CARE CONDITIONS :

Maintenance of hardwood floors with lacquer CosNanoTech+ finish assumes regular (daily if necessary) cleaning from dust and dirt using a vacuum, followed by a thorough cleaning using Coswick hardwood floor cleaner or other similar product. Due to high wear resistance properties, CosNanoTech+ lacquer finish does not require any additional care or finish renewal throughout the entire life of the floor.

GRADE : SELECT & BETTER

DESCRIPTION :		DESCRIPTION :	
Sound sapwood	Permitted to 25% of the plank area	Bark pocket	Permitted up to 10 mm in length, up to 3 mm in width, filled
Colour variation	Permitted slight colour variation	Pith	Permitted healthy heart
Knot	Permitted up to 10 mm, filled	Slope of grain	Permitted
Checks	Not permitted	Medullary ray	Permitted